

MONOFOCAL LENS

MODEL	FOCAL LENGTH [MM]	IRIS RANGE	MOUNT	HORIZONTAL ANGLE OF VIEW			FILTER SIZE [MM]	DIMENSIONS (D×L) (W×H×L) [MM]	WEIGHT (G)	REMARKS
				1/4 FORMAT	1/3 FORMAT	1/2 FORMAT				

MANUAL IRIS

1/4 FORMAT

QS210(C40206)	2.2	1.0 - C	CS	92.60	---	---	---	36.8×36.3	44	
QS310(C40301)	3	1.0 - C	CS	64.24	---	---	---	36.8×33.8	40	
QS610(C40601)	6	1.0 - C	CS	34.83	---	---	---	36.8×33.8	37	

1/3 FORMAT

TS212A(C70214)	2.8	1.2 - C	CS	71.54	94.31	---	---	36.8×36.3	44	
TS320NX(C91665)	3.6	2.0	CS	53.90	72.00	---	---	30×8	20	FOR B/W CAMERA
TS412A(C70409)	4	1.2 - C	CS	49.18	63.89	---	---	36.8×33.8	39	
TS820NX(C91666)	8	2.0	CS	23.90	31.40	---	---	30×8	18	FOR B/W CAMERA
TS812A(C70807)	8	1.2 - C	CS	25.05	33.33	---	---	36.8×33.8	34	

1/2 FORMAT

HS316A(C60305)	3.7	1.6 - C	CS	53.54	71.02	93.65	30.5 P=0.5	32×35.7	34	
HS614B(C60622)	6	1.4 - C	CS	33.86	44.55	57.82	30.5 P=0.5	32×35.7	32	
HS1214D(C61217)	12	1.4 - C	CS	16.55	22.06	29.42	30.5 P=0.5	32×35.7	26	
H416(C60402)	4.2	1.6 - C	C	47.87	64.27	86.77	---	42×43.5	120	
H612A(C60607)	6	1.2 - C	C	32.97	43.55	56.93	40.5 P=0.5	42×46	125	LOCK SCREW EXTRA
H1212B(C61215)	12	1.2 - 22	C	16.93	22.60	30.18	27.0 P=0.5	30×35.5	67	LOCK SCREW EXTRA

2/3, 1 FORMAT

C418DX(C30405)	4.8	1.8 - C	C	41.68	55.11	72.37	---	40.5×35.5	105	LOCK SCREW EXTRA
B618CX-2(C20612)	6.5	1.8 - C	C	29.94	39.73	52.52	---	48×42	120	
C814(C30808)	8	1.4 - C	C	25.15	33.31	43.88	40.5 P=0.5	42×58	160	
C815B(C30811)	8.5	1.5 - C	C	24.02	31.87	42.09	40.5 P=0.5	42×40	120	LOCK SCREW EXTRA
B1214D-2(C21211)	12.5	1.4 - C	C	16.21	21.53	28.51	40.5 P=0.5	42×50	135	LOCK SCREW EXTRA
B1218-2(C21212)	12.5	1.8 - C	C	16.48	21.90	29.01	40.5 P=0.5	42×40	95	LOCK SCREW EXTRA
C1614A(C31630)	16	1.4 - 22	C	12.70	16.91	22.48	27.0 P=0.5	30×33	58	LOCK SCREW EXTRA
B2514D(C22525)	25	1.4 - 22	C	8.23	10.97	14.62	27.0 P=0.5	30×37.3	76	LOCK SCREW EXTRA
B2518(C22516)	25	1.8 - C	C	8.23	10.95	14.55	40.5 P=0.5	42×40	87	LOCK SCREW EXTRA
B5014A(C25011)	50	1.4 - C	C	4.13	5.50	7.32	46.0 P=0.75	48×48	180	LOCK SCREW EXTRA
B5018A-3(C25010)	50	1.8 - C	C	4.13	5.50	7.32	40.5 P=0.5	42×52.5	130	LOCK SCREW EXTRA
B7514C(C27509)	75	1.4 - C	C	2.75	3.67	4.90	58.0 P=0.75	62×79	450	LOCK SCREW EXTRA

MANUAL IRIS FOR MACHINE VISION

1/2 FORMAT

H1214-M(C61232)	12	1.4 - 16	C	16.49	21.88	28.91	27.0 P=0.5	29.5×28.5	55	LOCK SCREW
-----------------	----	----------	---	-------	-------	-------	------------	-----------	----	------------

2/3 FORMAT

C1614-M(C31634)	16	1.4 - 16	C	12.86	17.11	22.72	27.0 P=0.5	29.5×33.2	63	LOCK SCREW
C2514-M(C32500)	25	1.4 - 16	C	8.24	10.97	14.60	27.0 P=0.5	29.5×32	55	LOCK SCREW
C3516-M(C33500)	35	1.6 - 16	C	6.07	8.09	10.76	27.0 P=0.5	29.5×35.4	64	LOCK SCREW
C5028-M(C35001)	50	2.8 - 22	C	4.12	5.50	7.32	27.0 P=0.5	29.5×34	55	LOCK SCREW

New

MANUAL IRIS FOR LINE-SCAN CAMERAS

YF3528(C52915)	35	2.8 - 22	F	45	64.40	62 P=0.75	72×56.8	440	NOT FOR PHOTOGRAPHIC CAMERAS
YK3528(C52915)	35	2.8 - 22	K	45	64.40	62 P=0.75	72×57.8	440	
YF5028(C52893)	50	2.8 - 22	F	45	47.60	62 P=0.75	72×56.8	440	
YK5028(C52893)	50	2.8 - 22	K	45	47.60	62 P=0.75	72×57.8	440	

AUTO IRIS

1/4 FORMAT

QS210E(C40202)	2.2	1.0 - 200	CS	92.60	---	---	---	36.8×43.5×36.3	54	VIDEO & DC IRIS
QS310E(C40300)	3	1.0 - 200	CS	64.24	---	---	---	36.8×43.5×33.8	50	VIDEO & DC IRIS
QS610E(C40600)	6	1.0 - 200	CS	34.83	---	---	---	36.8×43.5×33.8	47	VIDEO & DC IRIS

1/3 FORMAT

TS212E(C70210)	2.8	1.2 - 200	CS	71.54	94.31	---	---	36.8×43.5×36.3	54	VIDEO & DC IRIS
TS412E(C70406)	4	1.2 - 200	CS	49.18	63.89	---	---	36.8×43.5×33.8	49	VIDEO & DC IRIS
TS812E(C70804)	8	1.2 - 200	CS	25.05	33.33	---	---	36.8×43.5×33.8	44	VIDEO & DC IRIS

MONOFOCAL LENS

MODEL	FOCAL LENGTH [MM]	IRIS RANGE	MOUNT	HORIZONTAL ANGLE OF VIEW			FILTER SIZE [MM]	DIMENSIONS (D×L) (W×H×L) [MM]	WEIGHT (G)	REMARKS
				1/4 FORMAT	1/3 FORMAT	1/2 FORMAT				

■ AUTO IRIS (CONTINUED)

1/2 FORMAT

HS316TE(C60310)	3.7	1.6 - 90	CS	53.54	71.02	93.65	34 P=0.5	42.8×47.1×36.5	57	VIDEO & DC IRIS
HS614TE(C60631)	6	1.4 - 90	CS	33.86	44.55	57.82	34 P=0.5	42.8×47.1×36.5	60	VIDEO & DC IRIS
HS1214TE(C61228)	12	1.4 - 90	CS	16.55	22.06	29.42	34 P=0.5	42.8×47.1×36.5	46	VIDEO & DC IRIS
HS316E(C60309)	3.7	1.6 - 300	CS	53.54	71.02	93.65	34 P=0.5	42.8×47.1×36.5	57	VIDEO & DC IRIS
HS614E(C60630)	6	1.4 - 300	CS	33.86	44.55	57.82	34 P=0.5	42.8×47.1×36.5	60	VIDEO & DC IRIS
HS1214E(C61227)	12	1.4 - 300	CS	16.55	22.06	29.42	34 P=0.5	42.8×47.1×36.5	46	VIDEO & DC IRIS
H416E(C60405)	4.2	1.6 - 360	C	47.87	64.27	86.77	---	46.5×50.5×45	135	VIDEO IRIS
H612E(C60625)	6	1.2 - 360	C	32.97	43.55	56.93	43 P=0.75	46.5×50.5×51.1	130	VIDEO IRIS
H1212E(C61220)	12	1.2 - 360	C	16.93	22.60	30.18	43 P=0.75	46.5×50.5×51.1	130	VIDEO IRIS

2/3, 1 FORMAT

C418E(C30407)	4.8	1.8 - 360	C	41.27	54.57	71.65	---	46.5×50.5×37.5	120	VIDEO IRIS
C814E(C30821)	8	1.4 - 360	C	25.10	33.22	43.67	43 P=0.75	46.5×50.5×51.1	140	VIDEO IRIS
B1214E(C21223)	12.5	1.4 - 360	C	16.21	21.53	28.51	43 P=0.75	46.5×50.5×47.5	140	VIDEO IRIS
C1614E(C31632)	16	1.4 - 360	C	12.70	16.91	22.48	43 P=0.75	46.5×50.5×46.7	110	VIDEO IRIS
B2514E(C22527)	25	1.4 - 360	C	8.23	10.97	14.62	43 P=0.75	46.5×50.5×51.8	140	VIDEO IRIS
B5018E(C25018)	50	1.8 - 360	C	4.13	5.50	7.32	49 P=0.75	62×51	230	VIDEO IRIS
B7518E(C27513)	75	1.8 - 360	C	2.76	3.67	4.90	49 P=0.75	62×70.5	300	VIDEO IRIS

■ ASPHERICAL, ULTRA-HIGH SPEED AUTO IRIS

1/3 FORMAT

TS209E-ASP(C70204)	2.8	0.95 - 180	CS	72.69	98.24	---	---	48×53×46.9	140	DC IRIS
TS407E-ASP(C70405)	4	0.75 - 180	CS	48.39	62.55	---	40.5 P=0.5	48×53×53.1	145	DC IRIS
TS807E-ASP(C70803)	8	0.75 - 180	CS	25.07	33.31	---	40.5 P=0.5	48×53×46.9	135	DC IRIS

■ MANUAL OVERRIDE (REMOTE-CONTROL IRIS)

1/2 FORMAT

H416ER(C60404)	4.2	1.6 - 360	C	47.87	64.27	86.77	---	46.5×50.5×45	135	
H612ER(C60624)	6	1.2 - 360	C	32.97	43.55	56.93	43 P=0.75	46.5×50.5×51.1	140	
H1212ER(C61219)	12	1.2 - 360	C	16.93	22.60	30.18	43 P=0.75	46.5×50.5×51.1	140	

2/3, 1 FORMAT

C418ER(C30406)	4.8	1.8 - 360	C	41.27	54.57	71.65	---	46.5×50.5×37.5	120	
C814ER(C30820)	8	1.4 - 360	C	25.10	33.22	43.67	43 P=0.75	46.5×50.5×51.1	140	
B1214ER(C21221)	12.5	1.4 - 360	C	16.21	21.53	28.51	43 P=0.75	46.5×50.5×47.5	140	
C1614ER(C31631)	16	1.4 - 360	C	12.70	16.91	22.48	43 P=0.75	46.5×50.5×46.7	110	
B2514ER(C22526)	25	1.4 - 360	C	8.23	10.97	14.62	43 P=0.75	46.5×50.5×51.8	140	
B5018ER(C25017)	50	1.8 - 360	C	4.13	5.50	7.32	49 P=0.75	62×51	210	

■ AUTO IRIS FOR HIGH SENSITIVITY CAMERA

1 FORMAT

B1214E-2000(C21224)	12.5	1.4 - 2000	C	16.21	21.53	28.51	43 P=0.75	46.5×50.5×47.5	140	VIDEO IRIS
B2514E-2000(C22528)	25	1.4 - 2000	C	8.23	10.97	14.62	43 P=0.75	46.5×50.5×51.8	140	VIDEO IRIS
B5018E-1000(C25019)	50	1.8 - 1000	C	4.13	5.50	7.32	49 P=0.75	62×51	215	VIDEO IRIS
B7518E-1000(C27514)	75	1.8 - 1000	C	2.76	3.67	4.90	49 P=0.75	62×70.5	295	VIDEO IRIS

■ MANUAL IRIS & AUTO IRIS PINHOLE

1/3 FORMAT

TS420P(C70404)	4	2.0 - C	CS	51.24	68.47	---	---	36.5×65.9	74	MANUAL IRIS
TS420PE(C70403)	4	2.0 - 64	CS	51.24	68.47	---	---	36.5×42.3×65.9	79	DC IRIS

1/2 FORMAT

HS620P(C60613)	6.2	2.0 - C	CS	32.44	42.82	56.12	---	29×88.1	67	MANUAL IRIS
H620P(C60612)	6.2	2.0 - C	C	32.44	42.82	56.12	---	29×83.1	63	MANUAL IRIS
HS620PE(C60627)	6.2	2.0 - 300	CS	32.44	42.82	56.12	---	39×45.5×88.2	105	VIDEO & DC IRIS
H620PE(C60626)	6.2	2.0 - 300	C	32.44	42.82	56.12	---	39×45.5×83.2	100	VIDEO & DC IRIS

2/3 FORMAT

C934P(C30900)	9	3.4 - 22	C	22.30	29.60	39.11	---	34×164	175	MANUAL IRIS
C934PL(C30901)	9	3.4 - 22	C	22.30	29.60	39.11	---	---	210	R/A, MANUAL IRIS

ZOOM LENS

MODEL	FOCAL	IRIS RANGE	MOUNT	HORIZONTAL ANGLE OF VIEW			FILTER SIZE [MM]	DIMENSIONS (D×L) (W×H×L) [MM]	WEIGHT (G)	REMARKS
				1/4 FORMAT	1/3 FORMAT	1/2 FORMAT				

MANUAL IRIS VARI-FOCAL

1/4 FORMAT

QS2V2212	2.2 - 4.5	1.2 - C	CS		---	---				COMING SOON
QS2V2812(C40207)	2.8 - 5.8	1.2 - C	CS	76.21 - 36.41	---	---	30.5 P=0.5	36×43.5	45	

1/3 FORMAT

TS2V214(C70213)	2.8 - 6	1.4 - C	CS	72.46 - 35.15	96.94 - 46.74	---	---	36×43.2	47	
New TS2V314B(C70313)	3.5 - 8	1.4 - C	CS	58.74 - 26.55	79.83 - 35.44	---	30.5 P=0.5	36×43.5	43	
TS2V616(C70612)	6 - 12	1.6 - C	CS	34.92 - 17.21	47.22 - 22.97	---	30.5 P=0.5	36×43.5	43	

AUTO IRIS VARI-FOCAL

1/4 FORMAT

QS2V2212E	2.2 - 4.5	1.2 - 200	CS		---	---				COMING SOON
QS2V2812E(C40205)	2.8 - 5.8	1.2 - 200	CS	76.21 - 36.41	---	---	30.5 P=0.5	40.4×45.7×43.5	57	DC IRIS

1/3 FORMAT

TS2V114E(C70100)	1.6 - 3.4	1.4 - 64	CS	180.00 - 64.89	180.00 - 89.55	---	---	38.3×44.7×56.7	140	FISH EYE, DC IRIS
TS2V214E(C70209)	2.8 - 6	1.4 - 200	CS	72.46 - 35.15	96.94 - 46.74	---	---	40.4×45.7×43.2	59	VIDEO & DC IRIS
New TS2V314BE(C70312)	3.5 - 8	1.4 - 300	CS	58.74 - 26.55	79.83 - 35.44	---	30.5 P=0.5	40.4×45.7×43.5	59	VIDEO & DC IRIS
TS2V616E(C70608)	6 - 12	1.6 - 200	CS	34.92 - 17.21	47.22 - 22.97	---	30.5 P=0.5	40.4×45.7×43.5	53	VIDEO & DC IRIS

MANUAL ZOOM

1/2 FORMAT

H6Z810(C60812)	8 - 48	1.0 - 22	C	24.92 - 4.42	32.99 - 5.86	43.26 - 7.73	55 P=0.75	57×95	430	
----------------	--------	----------	---	--------------	--------------	--------------	-----------	-------	-----	--

2/3 FORMAT

C6Z1218(C31204)	12.5 - 75	1.8 - 22	C	16.08 - 2.75	21.40 - 3.66	28.44 - 4.87	49 P=0.75	51×90	320	
-----------------	-----------	----------	---	--------------	--------------	--------------	-----------	-------	-----	--

MANUAL ZOOM (AUTO IRIS)

1/3 FORMAT

TS6ZE(C70605)	6.3 - 38	1.2 - 512	CS	31.26 - 5.59	41.12 - 7.43	---	49 P=0.75	57.5×77.8	320	VIDEO & DC IRIS
---------------	----------	-----------	----	--------------	--------------	-----	-----------	-----------	-----	-----------------

1/2 FORMAT

H6ZBE(C60811)	8 - 48	1.0 - 720	C	24.92 - 4.42	32.98 - 5.86	43.24 - 7.73	55 P=0.75	69×64×95	465	VIDEO IRIS
---------------	--------	-----------	---	--------------	--------------	--------------	-----------	----------	-----	------------

2/3 FORMAT

C6ZE(C31219)*	12.5 - 75	1.8 - 720	C	16.06 - 2.75	21.38 - 3.66	28.41 - 4.87	49 P=0.75	68×90	385	VIDEO IRIS
---------------	-----------	-----------	---	--------------	--------------	--------------	-----------	-------	-----	------------

MOTORIZED ZOOM (MOTORIZED IRIS)

2/3 FORMAT

C6Z1218M3(C31211)	12.5 - 75	1.8 - C	C	16.06 - 2.75	21.38 - 3.66	28.41 - 4.87	49 P=0.75	101.5×92.2×94.5	820	
-------------------	-----------	---------	---	--------------	--------------	--------------	-----------	-----------------	-----	--

MOTORIZED ZOOM (AUTO IRIS)

1/4 FORMAT

QS6ZME(C40400)	4.6 - 28	1.0 - 250	CS	41.64 - 7.50	---	---	49 P=0.75	65×72.8×77	430	VIDEO & DC IRIS
----------------	----------	-----------	----	--------------	-----	-----	-----------	------------	-----	-----------------

1/3 FORMAT

TS6ZME(C70600)	6.3 - 38	1.2 - 360	CS	31.26 - 5.59	41.12 - 7.43	---	49 P=0.75	58×63.5×78	410	VIDEO & DC IRIS
TS10ZME(C70500)*	5.8 - 58	1.2 - 360	CS	33.77 - 3.62	44.07 - 4.78	---	49 P=0.75	64.6×70.3×85	380	VIDEO & DC IRIS
TS15ZME(C70601)*	6 - 90	1.2 - 720	CS	32.96 - 2.33	43.48 - 3.08	---	62 P=0.75	78×88.5×119	760	VIDEO & DC IRIS
TS20ZME(C70900)*	9 - 180	1.2 - 510	CS	22.61 - 1.15	30.28 - 1.53	---	95 P=1.0	116×135×216	2590	VIDEO & DC IRIS

1/2 FORMAT

HS6ZME(C60806)	8 - 48	1.4 - 360	CS	24.81 - 4.39	32.78 - 5.82	42.88 - 7.69	49 P=0.75	58×63.5×78	400	VIDEO & DC IRIS
HS10ZME(C60700)	7.5 - 75	1.4 - 360	CS	26.15 - 2.83	34.52 - 3.75	45.05 - 4.95	58 P=0.75	67×75×112	580	VIDEO & DC IRIS
H6ZBME(C60809)*	8 - 48	1.0 - 720	C	24.92 - 4.42	32.98 - 5.86	43.24 - 7.73	55 P=0.75	64×74.5×97	530	VIDEO IRIS
H10ZME(C60701)*	7.5 - 75	1.2 - 512	C	26.45 - 2.84	34.94 - 3.77	45.63 - 4.99	62 P=0.75	70×80.5×121.5	715	VIDEO IRIS
H15ZME(C60817)*	8 - 120	1.6 - 1000	C	24.76 - 1.76	32.85 - 2.34	43.37 - 3.09	62 P=0.75	78×88.5×134	800	VIDEO IRIS
H20ZME(C61221)*	12 - 240	1.6 - 720	C	17.17 - 0.88	22.95 - 1.17	30.78 - 1.56	95 P=1.0	116×135×216	2590	VIDEO IRIS

2/3, 1 FORMAT

C6ZAME(C31220)*	12.5 - 75	1.8 - 720	C	16.06 - 2.75	21.38 - 3.66	28.41 - 4.87	49 P=0.75	101.5×92.2×94.5	620	VIDEO IRIS
C10ZAME(C31002)*	10.5 - 105	1.4 - 1000	C	18.97 - 2.02	25.24 - 2.68	33.49 - 3.56	72 P=0.75	121×109.5×149.5	1380	VIDEO IRIS
C14ZME(C31009)*	10 - 140	1.9 - 720	C	19.89 - 1.52	26.41 - 2.02	34.96 - 2.68	86 P=1.0	128×118.6×165	2000	VIDEO IRIS
B12ZCME(C21517)*	15 - 180	1.9 - 1400	C	13.29 - 1.18	17.69 - 1.57	23.54 - 2.09	107 P=1.0	145×137.5×227	3070	VIDEO IRIS

ZOOM LENS

MODEL	FOCAL LENGTH [MM]	IRIS RANGE	MOUNT	HORIZONTAL ANGLE OF VIEW			FILTER SIZE [MM]	DIMENSIONS (D×L) (W×H×L) [MM]	WEIGHT (G)	REMARKS
				1/4 FORMAT	1/3 FORMAT	1/2 FORMAT				
■ MOTORIZED ZOOM (PRE-SET/AUTO IRIS)										
1/4 FORMAT										
QS6ZME-P(C40401)*	4.6 - 28	1.0 - 250	CS	41.64 - 7.50	---	---	49 P=0.75	65×72.8×77	460	VIDEO & DC IRIS
1/3 FORMAT										
TS10ZME-P(C70501)*	5.8 - 58	1.2 - 360	CS	33.77 - 3.62	44.07 - 4.78	---	49 P=0.75	64.6×70.3×85	430	VIDEO & DC IRIS
TS15ZME-P(C70604)*	6 - 90	1.2 - 720	CS	32.96 - 2.33	43.48 - 3.08	---	62 P=0.75	78×88.5×119	770	VIDEO & DC IRIS
TS20ZME-P(C70903)*	9 - 180	1.2 - 510	CS	22.61 - 1.15	30.28 - 1.53	---	95 P=1.0	116×135×216	2620	VIDEO & DC IRIS
1/2 FORMAT										
H6ZBME-P(C60810)*	8 - 48	1.0 - 720	C	24.92 - 4.42	32.98 - 5.86	43.24 - 7.73	55 P=0.75	64×74.5×97	540	VIDEO IRIS
H10ZME-P(C60702)*	7.5 - 75	1.2 - 512	C	26.45 - 2.84	34.94 - 3.77	45.63 - 4.99	62 P=0.75	70×80.5×121.5	740	VIDEO IRIS
H15ZME-P(C60820)*	8 - 120	1.6 - 1000	C	24.76 - 1.76	32.85 - 2.34	43.37 - 3.09	62 P=0.75	78×88.5×134	810	VIDEO IRIS
H20ZME-P(C61224)*	12 - 240	1.6 - 720	C	17.17 - 0.88	22.95 - 1.17	30.78 - 1.56	95 P=1.0	116×135×216	2620	VIDEO IRIS
New H55ZME-P(C61234)*	12 - 1320	4.0 - 360	C	17.17 - 0.16	23.18 - 0.21	31.65 - 0.28	105 P=1.0	155×137×356	5400	VIDEO IRIS 2X EXTENDER
2/3, 1 FORMAT										
C6ZME-P(C31221)	12.5 - 75	1.8 - 720	C	16.06 - 2.75	21.38 - 3.66	28.41 - 4.87	49 P=0.75	101.5×92.2×94.5	655	VIDEO IRIS
C10ZAME-P(C31003)*	10.5 - 105	1.4 - 1000	C	18.97 - 2.02	25.24 - 2.68	33.49 - 3.56	72 P=0.75	121×109.5×149.5	1420	VIDEO IRIS
C14ZME-P(C31010)*	10 - 140	1.9 - 720	C	19.89 - 1.52	26.41 - 2.02	34.96 - 2.68	86 P=1.0	128×118.6×165	2040	VIDEO IRIS
B12ZCME-P(C21520)*	15 - 180	1.9 - 1400	C	13.29 - 1.18	17.69 - 1.57	23.54 - 2.09	107 P=1.0	145×137.5×227	3150	VIDEO IRIS

■ **MOTORIZED ZOOM LENS (PRE-SET/AUTO IRIS & MANUAL OVERRIDE)**
MANUAL OVERRIDE OPTION IS AVAILABLE ON THE MODELS ASTERISKED (*)

COSMICAR / PENTAX

ACCESSORY

ITEM	MODEL NUMBER	REMARKS
2X EXTENDER	2-EX(C80001)	Rear conversion lens to double the focal length.
	S2-EX(C80034)	[2-EX: For C-Mount lenses, S2-EX: For CS-Mount lenses]
MACRO-FOCUS RING	EX-C6(C90100)	6 different length of rings to adjust the focal point for the close-up application
	RR-27(C80036)	Reverse ring to mount lenses in reverse on cameras for the close-up application
	RR-40.5(C80037)	Especially recommended where magnification of 1× or more is required
WIDE ATTACHMENT	WA-2(C80027)	Front attachment lens to widen the angle of view without reducing the aperture ratio [WA-2: H612E, C814E, B1214E]
	WA-5(C80033)	[WA-5: HS316TE, HS316E, HS614TE, HS614E, HS1214TE, HS1214E]
MOUNT ADAPTER	PC-MOUNT(C80018)	Adapter for Pentax P-Mount lens to be used with C-Mount camera
	KC-MOUNT(C80020)	Adapter for Pentax K-Mount lens to be used with C-Mount camera
DUMMY LENS	DM-163(C80029/C80039)	Dummy camera lens
	DM-E01(C80040)	[DM-163: Manual iris type, DM-E01: Auto iris type]
FILTER		Various kinds of optical filters and accessories are available